

Kehong Enterprises Co.,Ltd.

Website: www.khenterprise.en.alibaba.com

Mail: lily@gzhelectric.com

Tel:+86-20-82586869, Mobile: +8615918777767

Cold Shrink Tube

Model: SRCST



Made of silicone rubber
Offering good mechanical, insulation and sealing protection
Accommodating a wide range of cable sizes
For indoor or outdoor applications
Simple and fast installation
Color: Gray/Black

Selection Table

Size(ID, mm)	Fit for Cable OD(mm)	After full recovery Length(mm)
Φ25	7.3-21	81.3
Φ25	7.3-21	178
Φ25	7.3-21	203
Φ28	6-25.	125
Φ28	6-25.	150
Φ35	10.5-30	178
Φ35	10.5-30	229
Φ35	10.5-30	254
Φ35	10.5-30	305
Φ40	11.9-34	140
Φ40	11.9-34	203
Φ40	11.9-34	230
Φ40	11.9-34	254
Φ40	11.9-34	305
Φ45	13.5-39	152
Φ45	13.5-39	178

Kehong Enterprises Co.,Ltd.

Website: www.khenterprise.en.alibaba.com

Mail: lily@gzhelectric.com

Tel:+86-20-82586869, Mobile: +8615918777767

Φ45	13.5-39	203
Φ45	13.5-39	254
Φ45	13.5-39	305
Φ53	18.2-45	152
Φ53	18.2-45	254
Φ53	18.2-45	305
Φ53	18.2-45	457
Φ70	22.4-63	125
Φ70	22.4-63	152
Φ70	22.4-63	254
Φ70	22.4-63	355
Φ70	22.4-63	457
Φ70	22.4-63	508

Technical Features

Property	Test Method	Unit	Typical value
Color			Gray/Black
Density	GB/T1033-2008	g/cm ³	1.11
Shore A Hardness	ASTM D2240		43
Tensile strength(single)	ASTM D412	Mpa	8.5 min.
Elongation at Break	ASTM D412	%	670
Tear Strength	ASTM D624	Kn/mm	25
Volume resistivity	IEC 60093	Ω.cm	9*10 ¹⁵
Protection performance	IEC60529		IP 67
Ozone Aging	ISO 1431		No crack
Fungus Resistance	IEC60068		Grade 0